



CORE FROZR L



Product Specifications	
Model Name	Core Frozr L
Dimensions	140mm x 155mm x 55mm (w/o Fan)
	140mm x 155mm x 84mm (w/ single TORX Fan)
	120mm x 120mm x 25.6mm (TORX Fan)
Heat Pipes	8mm copper pipes x 4
Socket	Intel LGA 2066/2011-3/2011/1366/1156/ 1155/1151/1150/775
	AMD AM4/FM2/FM1/AM3+/AM3/AM2+/AM2
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Noise Level (Fans)	17.2 ~ 33.6 dBA
Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
Thermal Grease	Premium thermal compound X
Weight	775 g(w/o single TORX Fan)
	960 g (w/ single TORX Fan)
	1555 g(Completed packaging)

- Nickel-plated copper base connected with four highly efficient 8mm heat pipes and aluminum fins to dissipate up to 200W of heat from the CPU
- Premium Thermal Compound X ensures lasting heat conductivity
- Airflow control technology uses special deflectors in the fins to direct more air onto the heat pipes for better cooling.
- 120mm Fan featuring the award-winning MSI TORX design uses Hydro-dynamic bearing to increase airflow
- 2 sets of Fan clips compatible with 120mm, allowing for dual-fan setup in push/pull configuration
- Smart base design leaves space for graphics card on 1st PCI-e slot
- Easy to install and compatible with all Intel and AMD platforms
- Metal CPU cooler backplate for extra toughness to prevent motherboard bending through long term usage
- Customizable cover panels in black & silver included in the box featuring the MSI GAMING shield LED